

M&J
Eta®PreShred series – stationary

Table of models and output figures



Type		M&J Eta®PreShred 1000	M&J Eta®PreShred 2000	M&J Eta®PreShred 4000	M&J Eta®PreShred 6000
Specification					
Overall dimension std (LxWxH)	mm	9000 x 2100 x 3000	9700 x 2300 x 3350	9700 x 2300 x 3500	11550 x 2700 x 4150
Weight in total	ton	13.2 - 16.0	14.3 - 16.4	20.5 - 23.5	34.3 - 39.2
Standard colour	RAL	7011, 9002	7011, 9002	7011, 9002	7011, 9002
Loading height (without hopper)	mm	3000	3350	3500	4150
Power Pack					
Overall dimension std (LxWxH)	mm	3000 x 2188 x 2108	3375 x 2188 x 2108	3375 x 2188 x 2108	3375 x 2188 x 2108
Electric motor	kW	2x55 / 2x75 / 2x110	1x110 / 1x132 / 1x200	2x132 / 2x160 / 2x200	2x200 / 2x250
Electric control unit		PLC	PLC	PLC	PLC
Drive principle		Double hydrostatic transmission	Hydrostatic transmission	Double hydrostatic transmission	Double hydrostatic transmission
Weight	ton	2.3 - 3.3	2.2 - 2.5	3.7 - 4.2	4.2 - 5.7
Cutting Table					
Number of shafts	Asynchronous drive	2	1	2	2
Rotating speed*	rpm	13-52 / 10-37	16-40 / 26-55	16-40 / 26-55	11-32
Number of knives		4 / 5 / 6 / 7	6 / 8 / 9 / 10	5 / 6 / 8 / 9 / 10 / 12	9 / 12 / 14 / 16
Number of counter knives		8 / 10 / 12 / 14	12 / 16 / 18 / 20	10 / 12 / 16 / 18 / 20 / 24	18 / 24 / 28 / 32
Cutting area (LxW)	mm	1584 x 1600	2420 x 1273	2420 x 2000	3461 x 2400
Weight	ton	7.9 - 8.7	8.7 - 10.2	12.5 - 14.9	24.5 - 27.7
Chassis					
Standard belt conveyor (LxW)	mm	4500 x 1200	4500 x 1200	4500 x 1200	6500 x 1200
Discharge height	mm	1145	1145	1145	1145
Discharge width	mm	1200	1200	1200	1200
Weight (incl/excl conveyor)	ton	2.1 / 1.1	2.6 / 1.6	2.8 / 1.8	4.5 / 3.3

* standard/HDC power pack

M&J

Eta®PreShred series – stationary

Table of models and output figures



Metso Denmark A/S

Vejlevej 5

8700 Horsens

Denmark

E-Mail: recycling.info.dk@metso.com

www.metso.com/recycling/waste

